REAGENTS DUKSAN

SAFETY DATA SHEET

Vinyl Acetate monomer

Date of issue: 2019-10-01 **Revision date: 2019-10-01** **Version: R0001.0003**

1. IDENTIFICATION

A. Product name

- Vinyl Acetate monomer

B. Recommended use and restriction on use

- General use : for experimental, research and industrial use
- Restriction on use : Never drink, Not used except for experimental, research and industrial applications.

C. Manufacturer / Supplier / Distributor information

○ **Manufacturer information**

- Company name :
- Address :
- Emergency telephone number :

○ **Supplier/Distributer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, KOREA
- Telephone number : 82-31-495-4055
- Emergency telephone number : 82-31-495-4055 (08:30~17:30)
- Fax number : 82-31-495-4058


2. HAZARD IDENTIFICATION

A. GHS Classification

- Flammable liquids : Category2
- Acute toxicity (inhalation: vapor) : Category4
- Carcinogenicity : Category2
- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)
- Chronic aquatic toxicity : Category2

B. GHS label elements

○ **Hazard symbols**



○ **Signal words**

- Danger

○ **Hazard statements**

- H225 Highly flammable liquid and vapour
- H332 Harmful if inhaled
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer
- H411 Toxic to aquatic life with long lasting effects

○ **Precautionary statements**

1) Prevention

- P201 Obtain special instructions before use.

- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

2) Response

- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
- P391 Collect spillage.

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

○ **NFPA grade (0 ~ 4 level)**

- Health : 2 , Flammability : 3, Reactivity : 2

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Vinyl acetate	Acetic acid ethenyl ester ; Vinyl acetate monomer ; 1-Acetoxyethylene ; Acetoxyethene ; Acetoxyethylene	108-05-4	100

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Avoid inhalation of materials or combustion by-products.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- Due to the extremely low flash point, irrigating fire extinguishing may be less effective when put out a fire.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Do not direct water at spill or source of leak.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away,isolate hazard area and deny entry.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.
- Disposal of waste shall be in compliance with the Wastes Control?Act
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Since emptied containers retain product residue(vapor, liquid, solid) follow all MSDS and label warnings even after container is emptied.
- Do not handle until all safety precautions have been read and understood.
- Operators should wear antistatic footwear and clothing.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Do not use damaged containers.
- Do not apply direct heat.
- Do not apply any physical shock to container.
- Avoid direct sunlight.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

○ **ACGIH TLV**

- [Vinyl acetate] : TWA 10 ppm (35 mg/m3) STEL 15 ppm (53 mg/m3)

○ **OSHA PEL**

- Not available

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

○ **Respiratory protection**

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

○ **Eye protection**

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

○ **Hand protection**

- Wear appropriate chemical resistant glove.

○ **Skin protection**

- Wear appropriate chemical resistant protective clothing.

○ **Others**

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	colorless
B. Odor	characteristic odor

C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-93 ℃
F. Initial Boiling Point/Boiling Ranges	72 ℃
G. Flash point	-7 ℃
H. Evaporation rate	8.9
I. Flammability(solid, gas)	inflammability
J. Upper/Lower Flammability or explosive limits	13.4 / 2.6 %
K. Vapour pressure	11.7 ㎪ (20℃)
L. Solubility	2.5 g/100㎖ (20℃, ethane, ether, acetone, benzene, chloroform)
M. Vapour density	3
N. Specific gravity(Relative density)	0.9
O. Partition coefficient of n-octanol/water	0.73
P. Autoignition temperature	402 ℃
Q. Decomposition temperature	Not available
R. Viscosity	0.43 cP (20℃)
S. Molecular weight	86.09

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

○ **(Respiratory tracts)**

- May cause respiratory irritation.

○ **(Oral)**

- Not available

○ **(Eye·Skin)**

- Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

○ **Acute toxicity**

*** Oral**

- [Vinyl acetate] : LD50 3470 ㎎/㎏ Rat (ECHA)

*** Dermal**

- [Vinyl acetate] : LD50 2335 ㎎/㎏ Rabbit (NITE), LD50 7440 ㎎/㎏ Rat (ECHA)

*** Inhalation**

- [Vinyl acetate] : vapor LC50 14.084 ㎎/ℓ 4 hr Rat (ECHA)

○ **Skin corrosion/irritation**

- Not available

○ **Serious eye damage/irritation**

- Not available

○ **Respiratory sensitization**

- Not available

○ **Skin sensitization**

- Not available

○ **Carcinogenicity**

*** IARC**

- [Vinyl acetate] : Group 2B

*** OSHA**

- Not available

*** ACGIH**

- [Vinyl acetate] : A3

*** NTP**

- Not available

*** EU CLP**

- Not available

○ **Germ cell mutagenicity**

- Not available

○ **Reproductive toxicity**

- Not available

○ **STOT-single exposure**

- May cause respiratory irritation.

○ **STOT-repeated exposure**

- Not available

○ **Aspiration hazard**

- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- Not available

○ **Crustaceans**

- [Vinyl acetate] : EC50 12.6 ㎎/ℓ 48 hr Daphnia magna (ECHA)

○ **Algae**

- [Vinyl acetate] : EC50 8.81 ㎎/ℓ 72 hr Pseudokirchnerella subcapitata (ECHA)

B. Persistence and degradability

○ **Persistence**

- [Vinyl acetate] : log Kow 0.73 (ICSC)

○ **Degradability**

- Not available

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- Not available

○ **Biodegration**

- Not available

D. Mobility in soil

- [Vinyl acetate] : Koc 24.21 (Estimate)

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- It shall be treated by incineration

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 1301

B. Proper shipping name

- VINYL ACETATE, STABILIZED

C. Hazard Class

- 3

D. IMDG CODE/IATA DGR Packing group

- II

E. Marine pollutant

- Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-D (Flammable liquids)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ **POPs Management Law**

- Not applicable

○ **Information of EU Classification**

*** Classification**

- [Vinyl acetate] : H225

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- [Vinyl acetate] : 2267.995 kg 5000 lb

*** EPCRA Section 302 (40CFR355.30)**

- [Vinyl acetate] : 453.599 kg 1000 lb

*** EPCRA Section 304 (40CFR355.40)**

- [Vinyl acetate] : 2267.995 kg 5000 lb

*** EPCRA Section 313 (40CFR372.65)**

- [Vinyl acetate] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2019-10-01

C. Revision number and Last date revised

- 2 times, 2019-10-01

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).