REAGENTS DUKSAN

SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

Selenium

Date of issue: 2020-10-30 **Revision date: 2026-05-08** **Version: R0003.0001**

1. IDENTIFICATION

A. Product name

- Selenium

B. Recommended use and restriction on use

- General use : for experimental, research and industrial use
- Restriction on use : Never drink, Not used except for experimental, research and industrial applications.

C. Manufacturer / Supplier / Distributor information

○ **Manufacturer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, REPUBLIC OF KOREA
- Emergency telephone number : 82-31-495-4055

○ **Supplier/Distributer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, REPUBLIC OF KOREA
- Telephone number : 82-31-495-4055
- Emergency telephone number : 82-31-495-4055
- Fax number : 82-31-495-4058

2. HAZARD IDENTIFICATION

A. GHS Classification

- Acute toxicity (oral) : Category3
- Acute Toxicity (Inhalation: dust / mist) : Category3
- Specific target organ toxicity(Repeated exposure) : Category2
- Chronic aquatic toxicity : Category2

B. GHS label elements

○ **Hazard symbols**



○ **Signal words**

- Danger

○ **Hazard statements**

- H301 Toxic if swallowed
- H331 Toxic if inhaled
- H373 May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)
- H411 Toxic to aquatic life with long lasting effects

○ **Precautionary statements**

1) Prevention

- P260 Do not breathe dust/fume.
- P261 Avoid breathing dust/fume.

- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P311 Call a POISON CENTER or doctor/physician.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment
- P330 Rinse mouth.
- P391 Collect spillage.

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Selenium	Selenium alloy ; Selenium dust ; Elemental selenium	7782-49-2	100

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.
- Take the doctor's examination.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Flush skin with plenty of wter for at least 15 minutes while removing contaminated clothing and shoes.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Move containers from fire area, if you can do without the risk.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Wear proper personal protective apparatus as indicated in Section 8 and avoid skin contact and inhalation.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.
- Disposal of waste shall be in compliance with the Wastes Control?Act
- Appropriate container for disposal of spilled material collected.
- Small liquid state spills: Appropriate container for disposal of spilled material collected.
- Put the spilled material in an appropriate containers and clean the contaminated area
- Prevent the influx to waterways, sewers, basements or confined spaces.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Comply with all applicable laws and regulations for handling
- Refer to Engineering controls and personal protective equipment.
- Operators should wear antistatic footwear and clothing.

B. Conditions for safe storage, including any incompatibilities

- Do not use damaged containers.
- Avoid direct sunlight.
- Keep in the original container.
- Please pay attention to incompatibilities materials and conditions to avoid.
- No open fire.
- Collected them in sealed containers.
- Do not eat, drink or smoke when using this product.
- Store away from water and sewer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

○ **ACGIH TLV**

- [Selenium] : TWA 0.2 mg/m3, as Se

○ **OSHA PEL**

- [Selenium]: 0.2mg/m3

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

○ **Respiratory protection**

- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Dust, mist, fume-purifying respiratory protection
- Air-purifying respirator with high-efficiency particulate filtering
- Any respiratory protection with a electromotion fan(for dust, mist, fume-purifying)
- Self-contained breathing apparatus with a corpuscle filter of high efficiency
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

○ **Eye protection**

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

○ **Hand protection**

- Wear appropriate glove.

○ **Skin protection**

- Wear appropriate clothing.

○ **Others**

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Solid(Other)
- Color	dark gray
B. Odor	odorless
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	221 ℃
F. Initial Boiling Point/Boiling Ranges	685 ℃
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	0.1 ㎩ (20℃)
L. Solubility	0.206 g/100㎖ (25℃)
M. Vapour density	Not available
N. Specific gravity(Relative density)	4.8
O. Partition coefficient of n-octanol/water	0.24 (estimate)
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	79

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

○ **(Respiratory tracts)**

- Not available

○ **(Oral)**

- Toxic if swallowed

○ **(Eye·Skin)**

- Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

○ **Acute toxicity**

*** Oral**

- [Selenium] : LD50 >5000 ㎎/㎏ Rat (OECD TG 401,GLP)

*** Dermal**

- Not available

*** Inhalation**

- [Selenium] : dust LC50 5.67 ㎎/ℓ 4 hr Rat (Fine powder, EPA OPP 81-3, GLP)

○ **Skin corrosion/irritation**

- Not available

○ **Serious eye damage/irritation**

- Not available

○ **Respiratory sensitization**

- Not available

○ **Skin sensitization**

- Not available

○ **Carcinogenicity**

*** IARC**

- [Selenium] : Group 3

*** OSHA**

- Not available

*** ACGIH**

- Not available

*** NTP**

- Not available

*** EU CLP**

- Not available

○ **Germ cell mutagenicity**

- Not available

○ **Reproductive toxicity**

- Not available

○ **STOT-single exposure**

- Not available

○ **STOT-repeated exposure**

- May cause damage to organs through prolonged or repeated exposure

○ **Aspiration hazard**

- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- [Selenium] : ECHA LC50 2 ㎎/ℓ 96 hr Pimephales promelas(OECD TG 203, GLP)

○ **Crustaceans**

- [Selenium] : LC50 >100 ㎎/ℓ 48 hr Daphnia magna(OECD TG 202, GLP)(ECHA)

○ **Algae**

- [Selenium] : ECHA ErC50 >0.0173 ㎎/ℓ 72 hr (pH 8, 8.3, 20.5 °COECD TG 201, GLP)

B. Persistence and degradability

○ **Persistence**

- Not available

○ **Degradability**

- Not available

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [Selenium] : BCF 42.5 (OECD Guideline 305 B)

○ **Biodegradation**

- Not available

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- It shall be treated by incineration
- Do disposal as neutralization, hydrolysis and oxidation-reduction.
- High temperature incinerating, high-temperature melt processing will be landfilled
- Solidification processing.

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 3283

B. Proper shipping name

- SELENIUM COMPOUND, SOLID, N.O.S.

C. Hazard Class

- 6.1

D. IMDG CODE/IATA DGR Packing group

- III

E. Marine pollutant

- Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-A (General fire schedule)
- EmS SPILLAGE SCHEDULE : S-A (Toxic substances)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ **POPs Management Law**

- [Selenium] : Not applicable

○ **Information of EU Classification**

*** Classification**

- [Selenium] : H331, H301, H373, H413

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- [Selenium] : 45.3599 kg 100 lb

*** EPCRA Section 302 (40CFR355.30)**

- Not applicable

*** EPCRA Section 304 (40CFR355.40)**

- Not applicable

*** EPCRA Section 313 (40CFR372.65)**

- [Selenium] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2020-10-30

C. Revision number and Last date revised

- 2 times, 2026-05-08

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).