REAGENTS DUKSAN

# SAFETY DATA SHEET

**According to OSHA Hazcom Standard 29 CFR 1910.1200**

## Sulfuric Acid 9%

**Date of issue: 2020-03-04** **Revision date: 2026-01-21** **Version: R0003.0001**

## 1. IDENTIFICATION

### A. Product name

- Sulfuric Acid 9%

### B. Recommended use and restriction on use

- General use : for experimental, research and industrial use
- Restriction on use : Never drink, Not used except for experimental, research and industrial applications.

### C. Manufacturer / Supplier / Distributor information

○ **Manufacturer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, KOREA
- Emergency telephone number : 82-31-495-4055

○ **Supplier/Distributer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, KOREA
- Telephone number : 82-31-495-4055
- Emergency telephone number : 82-31-495-4055
- Fax number : 82-31-495-4058

## 2. HAZARD IDENTIFICATION

### A. GHS Classification

- Corrosive to metals : Category1
- Skin corrosion/irritation : Category1A
- Serious eye damage/irritation : Category1
- Carcinogenicity : Category1A

### B. GHS label elements

○ **Hazard symbols**



○ **Signal words**

- Danger

○ **Hazard statements**

- H290 May be corrosive to metals
- H314 Causes severe skin burns and eye damage
- H318 Causes serious eye damage
- H350 May cause cancer

○ **Precautionary statements**

**1) Prevention**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.

- P234 Keep only in original container.
- P260 Do not breathe gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

**2) Response**

- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P310 Immediately call a POISON CENTER or doctor/physician.
- P321 Specific treatment
- P363 Wash contaminated clothing before reuse.
- P390 Absorb spillage to prevent material damage.

**3) Storage**

- P405 Store locked up.
- P406 Store in corrosive resistant container with a resistant inner liner.

**4) Disposal**

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

### C. Other hazards which do not result in classification

- Not available

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | Trade names and Synonyms | CAS No. | Content(%) |
|---|---|---|---|
| Water | Dihydrogen oxide ; Oxidane | 7732-18-5 | 91 |
| Sulfuric acid | Hydrogensulfate | 7664-93-9 | 9 |

## 4. FIRST AID MEASURES

### A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Remove contact lenses if worn.

### B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

### C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

### D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

### E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

### F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

## 5. FIREFIGHTING MEASURES

### A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

### B. Specific hazards arising from the chemical

- Not available

### C. Special protective actions for firefighters

- Move containers from fire area, if you can do without the risk.
- Keep unauthorized personnel out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.

## 6. ACCIDENTAL RELEASE MEASURES

### A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Must work against the wind, let the upwind people to evacuate.
- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away,isolate hazard area and deny entry.

### B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

### C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.
- Disposal of waste shall be in compliance with the Wastes Control?Act
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Spilled material should be treated as a potential risk of waste collected.

## 7. HANDLING AND STORAGE

### A. Precautions for safe handling

- Avoid direct physical contact.
- Since emptied containers retain product residue(vapor, liquid, solid) follow all MSDS and label warnings even after container is emptied.
- Refer to Engineering controls and personal protective equipment.
- Do not handle until all safety precautions have been read and understood.

- Do not inhale the steam prolonged or repeated.
- Avoid contact with strong oxidizing agent.
- Contaminated work clothing should not be allowed out of the workplace.

### B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Do not apply any physical shock to container.
- Keep sealed when not in use.
- No open fire.
- Prevent static electricity and keep away from combustible materials or heat sources.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Do not store in metal containers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### A. Exposure limits

○ **ACGIH TLV**

- [Sulfuric acid] : TWA 0.2 mg/m3, Thoracic particulate mass

○ **OSHA PEL**

- [Sulfuric acid]: 1mg/m3

### B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

### C. Individual protection measures, such as personal protective equipment

○ **Respiratory protection**

- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.

○ **Eye protection**

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

○ **Hand protection**

- Wear appropriate chemical resistant glove.

○ **Skin protection**

- Wear appropriate chemical resistant protective clothing.

○ **Others**

- Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| A. Appearance | |
| - Appearance | Liquid |
| - Color | colorless |
| B. Odor | odorless |
| C. Odor threshold | Not available |
| D. pH | <1 |
| E. Melting point/Freezing point | 0℃ |
| F. Initial Boiling Point/Boiling Ranges | > 100 ℃ |

| | |
|---|---|
| G. Flash point | Not available |
| H. Evaporation rate | Not available |
| I. Flammability(solid, gas) | Not available |
| J. Upper/Lower Flammability or explosive limits | Not available |
| K. Vapour pressure | Not available |
| L. Solubility | Not available |
| M. Vapour density | Not available |
| N. Specific gravity(Relative density) | 1.06 |
| O. Partition coefficient of n-octanol/water | Not available |
| P. Autoignition temperature | Not available |
| Q. Decomposition temperature | Not available |
| R. Viscosity | Not available |
| S. Molecular weight | 98.07 |

## 10. STABILITY AND REACTIVITY

### A. Chemical Stability

- Stable under normal conditions of use and storage.

### B. Possibility of hazardous reactions

- May be corrosive to metals.

### C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with metals.

### D. Incompatible materials

- Avoid contact with strong oxidizing agent and strong reducing agent.

### E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

## 11. TOXICOLOGICAL INFORMATION

### A. Information on the likely routes of exposure

○ **(Respiratory tracts)**

- Not available

○ **(Oral)**

- Not available

○ **(Eye·Skin)**

- Causes serious eye damage
- Causes severe skin burns and eye damage

### B. Delayed and immediate effects and also chronic effects from short and long term exposure

○ **Acute toxicity**

*** Oral**

- Product (ATEmix) : >5000mg/kg
- [Water] : LD50 > 90000 ㎎/㎏ Rat (KOSHA)
- [Sulfuric acid] : LD50 2140 ㎎/㎏ Rat (OECD TG 401)(ECHA)

*** Dermal**

- Not available

*** Inhalation**

- Product (ATEmix) : 2.0mg/L < ATEmix <= 10.0mg/L
- [Sulfuric acid] : LC50 0.375 ㎎/ℓ 4 hr Rat (Aerosol/OECD TG 403, Female/Male)

○ **Skin corrosion/irritation**

- Causes severe skin burns and eye damage

○ **Serious eye damage/irritation**

- Causes serious eye damage

○ **Respiratory sensitization**

- Not available

○ **Skin sensitization**

- Not available

○ **Carcinogenicity**

*** IARC**

- [Sulfuric acid] : NULL

*** OSHA**

- Not available

*** ACGIH**

- [Sulfuric acid] : A2 (When contained in strong inorganic acid mists)

*** NTP**

- Not available

*** EU CLP**

- Not available

○ **Germ cell mutagenicity**

- Not available

○ **Reproductive toxicity**

- Not available

○ **STOT-single exposure**

- Not available

○ **STOT-repeated exposure**

- Not available

○ **Aspiration hazard**

- Not available

## 12. ECOLOGICAL INFORMATION

### A. Ecotoxicity

○ **Fish**

- [Sulfuric acid] : LC50 16 ㎎/ℓ ~ 28 ㎎/ℓ 96 hr Lepomis macrochirus

○ **Crustaceans**

- [Sulfuric acid] : EC50 > 100 ㎎/ℓ 48 hr Daphnia magna (pH 7.9, OECD TG 202, GLP)

○ **Algae**

- [Sulfuric acid] : EC50 > 100 ㎎/ℓ 72 hr (Desmodesmus subspicatus (pH 5.1,growth rate) (OECD TG 201, GLP)

### B. Persistence and degradability

○ **Persistence**

- [Water] : log Kow = -1.38
- [Sulfuric acid] : log Kow -1.43 (SRC)

○ **Degradability**

- Not available

### C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [Sulfuric acid] : BCF 250

○ **Biodegration**

- Not available

### D. Mobility in soil

- Not available

### E. Other adverse effects

- Not available

## 13. DISPOSAL CONSIDERATIONS

### A. Disposal methods

- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- It shall be treated by incineration

### B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

## 14. TRANSPORT INFORMATION

### A. UN No. (IMDG CODE/IATA DGR)

- 2796

### B. Proper shipping name

- SULFURIC ACID WITH NOT MORE THAN 51% ACID

### C. Hazard Class

- 8

### D. IMDG CODE/IATA DGR Packing group

- II

### E. Marine pollutant

- Not applicable

### F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-A (General fire schedule)
- EmS SPILLAGE SCHEDULE : S-B (Corrosive substances)

## 15. REGULATORY INFORMATION

### A. National and/or international regulatory information

○ **POPs Management Law**

- Not applicable

○ **Information of EU Classification**

*** Classification**

- [Sulfuric acid] : H314

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- [Sulfuric acid] : 453.599 kg 1000 lb

*** EPCRA Section 302 (40CFR355.30)**

- [Sulfuric acid] : 453.599 kg 1000 lb

*** EPCRA Section 304 (40CFR355.40)**

- [Sulfuric acid] : 453.599 kg 1000 lb

*** EPCRA Section 313 (40CFR372.65)**

- [Sulfuric acid] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

## 16. OTHER INFORMATION

### A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

### B. Issue date

- 2020-03-04

### C. Revision number and Last date revised

- 2 times, 2026-01-21

### D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).