REAGENTS DUKSAN

SAFETY DATA SHEET

Iso-Propyl Alcohol 70% sterile

Date of issue: 2023-02-23 **Revision date: -** **Version: R0001.0001**

1. IDENTIFICATION

A. Product name

- Iso-Propyl Alcohol 70% sterile

B. Recommended use and restriction on use

- General use : for experimental, research and industrial use
- Restriction on use : Never drink, Not used except for experimental, research and industrial applications.

C. Manufacturer / Supplier / Distributor information

○ **Manufacturer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, KOREA
- Emergency telephone number : 82-31-495-4055

○ **Supplier/Distributer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, KOREA
- Telephone number : 82-31-495-4055
- Emergency telephone number : 82-31-495-4055
- Fax number : 82-31-495-4058

2. HAZARD IDENTIFICATION

A. GHS Classification

- Flammable liquids : Category2
- Serious eye damage/irritation : Category2A
- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)
- Aspiration hazard : Category2

B. GHS label elements

○ **Hazard symbols**



○ **Signal words**

- Danger

○ **Hazard statements**

- H225 Highly flammable liquid and vapour
- H305 May be harmful if swallowed and enters airways
- H319 Causes serious eye irritation
- H336 May cause drowsiness and dizziness.

○ **Precautionary statements**

1) Prevention

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P331 Do NOT induce vomiting.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

○ **NFPA grade (0 ~ 4 level)**

- Health : 2, Flammability : 3, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
2-Propanol	Isopropanol ; Dimethylcarbinol ; Isopropyl alcohol ; n-Propan-2-ol ; Propan-2-ol ; i-Propyl alcohol ; 2-Propanol	67-63-0	70
Water	Dihydrogen oxide ; Oxidane	7732-18-5	30

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.

- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Move containers from fire area, if you can do without the risk.
- Keep unauthorized personnel out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- Due to the extremely low flash point, irrigating fire extinguishing may be less effective when put out a fire.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid direct physical contact.

- Comply with all applicable laws and regulations for handling
- Do not handle until all safety precautions have been read and understood.
- Operators should wear antistatic footwear and clothing.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.

B. Conditions for safe storage, including any incompatibilities

- Save in cool, dry and well ventilated place.
- Do not use damaged containers.
- Store according to current laws and regulations
- Please pay attention to incompatibilities materials and conditions to avoid.
- Keep sealed when not in use.
- Collected them in sealed containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

○ **ACGIH TLV**

- [2-Propanol] : TWA, 200 ppm (491 mg/m3), STEL, 400 ppm (984 mg/m3)

○ **OSHA PEL**

- [2-Propanol]:400ppm 980mg/m3

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

○ **Respiratory protection**

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

○ **Eye protection**

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

○ **Hand protection**

- Wear appropriate chemical resistant glove.

○ **Skin protection**

- Wear appropriate chemical resistant protective clothing.

○ **Others**

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	colorless
B. Odor	alcohol odor
C. Odor threshold	22 ppm
D. pH	Not available
E. Melting point/Freezing point	-90 ℃
F. Initial Boiling Point/Boiling Ranges	83 ℃

G. Flash point	11.7 ℃
H. Evaporation rate	1.7 (n-butyl acetate=1)
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	12 / 2 %
K. Vapour pressure	4.4 ㎪ (20℃)
L. Solubility	100 g/100㎖
M. Vapour density	2.1
N. Specific gravity(Relative density)	0.79 (water=1)
O. Partition coefficient of n-octanol/water	0.05
P. Autoignition temperature	456 ℃
Q. Decomposition temperature	Not available
R. Viscosity	2.1 cP (25℃)
S. Molecular weight	60.1

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

○ **(Respiratory tracts)**

- May be harmful if swallowed and enters airways

○ **(Oral)**

- Not available

○ **(Eye·Skin)**

- Causes serious eye irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

○ **Acute toxicity**

*** Oral**

- Product (ATEmix) : 2000mg/kg < ATEmix <= 5000mg/kg
- [2-Propanol] : LD50 = 4710㎎/㎏ Rat (HSDB) LD50 5840 ㎎/㎏ Rat (OECD TG 401, ECHA)
- [Water] : LD50 > 90000 ㎎/㎏ Rat (KOSHA)

*** Dermal**

- Product (ATEmix) : >5000mg/kg
- [2-Propanol] : LD50 = 12870 ㎎/㎏ rabbit (HSDB), LD50 16400 ㎎/㎏ Rabbit (OECD TG402, ECHA)

*** Inhalation**

- Product (ATEmix) : >50.0mg/L
- [2-Propanol] : LC50 = 72.6 ㎎/ℓ 4 hr Rat (HSDB), LC50 >10000 ppm 6 hr Rat (OECE TG 403, GLP)

○ **Skin corrosion/irritation**

- Not available

○ **Serious eye damage/irritation**

- Causes serious eye irritation

○ **Respiratory sensitization**

- Not available

○ **Skin sensitization**

- Not available

○ **Carcinogenicity**

*** IARC**

- [2-Propanol] : Group 3

*** OSHA**

- Not available

*** ACGIH**

- [2-Propanol] : A4

*** NTP**

- Not available

*** EU CLP**

- Not available

○ **Germ cell mutagenicity**

- Not available

○ **Reproductive toxicity**

- Not available

○ **STOT-single exposure**

- May cause drowsiness and dizziness.

○ **STOT-repeated exposure**

- Not available

○ **Aspiration hazard**

- May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- [2-Propanol] : LC50 >100 ㎎/ℓ 96 hr Oryzias latipes (NITE: MOE eco-toxicity tests of chemicals, 1997)

○ **Crustaceans**

- [2-Propanol] : ECHA LC50 5102 ㎎/ℓ 24 hr Daphnia magna(OECD TG 202)

○ **Algae**

- [2-Propanol] : EC50 = 2.2 ㎎/ℓ 96 hr

B. Persistence and degradability

○ **Persistence**

- [Water] : log Kow = -1.38

○ **Degradability**

- Not available

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- Not available

○ **Biodegration**

- Not available

D. Mobility in soil

- [2-Propanol] : log koc= 0.03

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designated waste is mixed, it is difficult to treat separately, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- Will be pre-processed by the separation of oil and water.

B. Special precautions for disposal

- The user of this product must dispose by oneself or entrust it to a waste disposer, a person who recycles other's waste or establishes and operates waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 1219

B. Proper shipping name

- ISOPROPANOL OR ISOPROPYL ALCOHOL

C. Hazard Class

- 3

D. IMDG CODE/IATA DGR Packing group

- II

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-D (Flammable liquids)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ **POPs Management Law**

- Not applicable

○ **Information of EU Classification**

*** Classification**

- [2-Propanol] : H225, H319, H336

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- Not applicable

*** EPCRA Section 302 (40CFR355.30)**

- Not applicable

*** EPCRA Section 304 (40CFR355.40)**

- Not applicable

*** EPCRA Section 313 (40CFR372.65)**

- [2-Propanol] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2023-02-23

C. Revision number and Last date revised

- Not applicable

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).