REAGENTS DUKSAN

SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

Dibutyl Phthalate

Date of issue: 2020-01-20 **Revision date: 2023-07-28** **Version: R0003.0001**

1. IDENTIFICATION

A. Product name

- Dibutyl Phthalate

B. Recommended use and restriction on use

- General use : for experimental, research and industrial use
- Restriction on use : Never drink, Not used except for experimental, research and industrial applications.

C. Manufacturer / Supplier / Distributor information

○ **Manufacturer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, KOREA
- Emergency telephone number : 82-31-495-4055

○ **Supplier/Distributer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, KOREA
- Telephone number : 82-31-495-4055
- Emergency telephone number : 82-31-495-4055
- Fax number : 82-31-495-4058


2. HAZARD IDENTIFICATION

A. GHS Classification

- Reproductive toxicity : Category1B
- Acute aquatic toxicity : Category1

B. GHS label elements

○ **Hazard symbols**



○ **Signal words**

- Danger

○ **Hazard statements**

- H360 May damage fertility or the unborn child
- H400 Very toxic to aquatic life

○ **Precautionary statements**

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

2) Response

- P308+P313 If exposed or concerned: Get medical advice/attention.

- P391 Collect spillage.

3) Storage

- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Dibutyl phthalate	Di(n-butyl) 1,2-benzenedicarboxylate ; Bis-n-butyl phthalate ; Butyl phthalate ; n-Butyl phthalate ; Dibutyl 1,2-benzenedicarboxylate ; Dibutyl o-phthalate ; Di-n-butyl phthalate ;	84-74-2	100

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.
- Remove contaminated clothing, shoes and isolate.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Keep unauthorized personnel out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- Avoid inhalation of materials or combustion by-products.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Do not direct water at spill or source of leak.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away,isolate hazard area and deny entry.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.
- Disposal of waste shall be in compliance with the Wastes Control?Act
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Avoid entering to sewers or water system.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Since emptied containers retain product residue(vapor, liquid, solid) follow all MSDS and label warnings even after container is emptied.
- Do not handle until all safety precautions have been read and understood.
- Operators should wear antistatic footwear and clothing.
- Do not inhale the steam prolonged or repeated.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Do not use damaged containers.
- Do not apply direct heat.
- Do not apply any physical shock to container.
- Avoid direct sunlight.
- Collected them in sealed containers.
- Store away from water and sewer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

○ **ACGIH TLV**

- [Dibutyl phthalate] : TWA, 5 mg/m3

○ **OSHA PEL**

- [Dibutyl phthalate]: 5mg/m3

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

○ **Respiratory protection**

- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.

○ **Eye protection**

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

○ **Hand protection**

- Wear appropriate glove.

○ **Skin protection**

- Wear appropriate clothing.

○ **Others**

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	colorless to yellow
B. Odor	characteristic odor
C. Odor threshold	5 ppm
D. pH	Not available
E. Melting point/Freezing point	-35 ℃
F. Initial Boiling Point/Boiling Ranges	340 ℃
G. Flash point	157 ℃
H. Evaporation rate	0 (초산 뷰틸=1)
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	2.5 / 0.5 % (235℃)
K. Vapour pressure	0.0000201 ㎜Hg (25℃)
L. Solubility	0.041 g/100㎖ (25℃)
M. Vapour density	9.58
N. Specific gravity(Relative density)	1.05
O. Partition coefficient of n-octanol/water	4.72
P. Autoignition temperature	402 ℃
Q. Decomposition temperature	Not available
R. Viscosity	20.3 cP (20℃)
S. Molecular weight	278.3

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

○ **(Respiratory tracts)**

- Not available

○ **(Oral)**

- Not available

○ **(Eye·Skin)**

- Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

○ **Acute toxicity**

*** Oral**

- [Dibutyl phthalate] : LD50 6300 ㎎/㎏ Rat

*** Dermal**

- [Dibutyl phthalate] : LD50 > 20000 ㎎/㎏ Rabbit

*** Inhalation**

- [Dibutyl phthalate] : LC50 15.68 ㎎/ℓ/4hr Rat

○ **Skin corrosion/irritation**

- Not available

○ **Serious eye damage/irritation**

- Not available

○ **Respiratory sensitization**

- Not available

○ **Skin sensitization**

- Not available

○ **Carcinogenicity**

*** IARC**

- Not available

*** OSHA**

- Not available

*** ACGIH**

- Not available

*** NTP**

- Not available

*** EU CLP**

- Not available

○ **Germ cell mutagenicity**

- Not available

○ **Reproductive toxicity**

- May damage fertility or the unborn child

○ **STOT-single exposure**

- Not available

○ **STOT-repeated exposure**

- Not available

○ **Aspiration hazard**

- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- [Dibutyl phthalate] : LC50 0.46 ㎎/ℓ 96 hr (NITE)

○ **Crustaceans**

- [Dibutyl phthalate] : EC50 2.99 ㎎/ℓ 48 hr

○ **Algae**

- Not available

B. Persistence and degradability

○ **Persistence**

- [Dibutyl phthalate] : log Kow 4.72

○ **Degradability**

- Not available

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [Dibutyl phthalate] : BCF 176 (existing chemical safety inspections data)

○ **Biodegration**

- [Dibutyl phthalate] : BOD : 69 (%)(existing chemical safety inspections data)

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- It shall be treated by incineration
- Do disposal as neutralization, hydrolysis and oxidation-reduction.
- High temperature incinerating, high-temperature melt processing will be landfilled
- Solidification processing.

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 3082

B. Proper shipping name

- ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S.

C. Hazard Class

- 9

D. IMDG CODE/IATA DGR Packing group

- III

E. Marine pollutant

- Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-A (General fire schedule)
- EmS SPILLAGE SCHEDULE : S-F (Water-soluble marine pollutants)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ **POPs Management Law**

- Not applicable

○ **Information of EU Classification**

*** Classification**

- [Dibutyl phthalate] : H360Df, H400,

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- [Dibutyl phthalate] : 4.53599 kg 10 lb

*** EPCRA Section 302 (40CFR355.30)**

- Not applicable

*** EPCRA Section 304 (40CFR355.40)**

- Not applicable

*** EPCRA Section 313 (40CFR372.65)**

- [Dibutyl phthalate] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2020-01-20

C. Revision number and Last date revised

- 2 times, 2023-07-28

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).