REAGENTS DUKSAN

SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

Graphite powder

Date of issue: 2019-03-07 **Revision date: 2026-04-08** **Version: R0003.0001**

1. IDENTIFICATION

A. Product name

- Graphite powder

B. Recommended use and restriction on use

- General use : for experimental, research and industrial use
- Restriction on use : Never drink, Not used except for experimental, research and industrial applications.

C. Manufacturer / Supplier / Distributor information

○ **Manufacturer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, REPUBLIC OF KOREA
- Emergency telephone number : 82-31-495-4055

○ **Supplier/Distributer information**

- Company name : DUKSAN PURE CHEMICALS
- Address : 53,SINWONRO 133BEONGIL, DANWONGU, ANSANSHI, GYUNGGIDO, REPUBLIC OF KOREA
- Telephone number : 82-31-495-4055
- Emergency telephone number : 82-31-495-4055
- Fax number : 82-31-495-4058

2. HAZARD IDENTIFICATION

A. GHS Classification

- Self-heating substance and mixtures : Category2
- Acute Toxicity (Inhalation: dust / mist) : Category4
- Specific target organ toxicity(Repeated exposure) : Category2

B. GHS label elements

○ **Hazard symbols**



○ **Signal words**

- Warning

○ **Hazard statements**

- H252 Self-heating in large quantities; may catch fire
- H332 Harmful if inhaled
- H373 May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)

○ **Precautionary statements**

1) Prevention

- P235+P410 Keep cool. Protect from sunlight.
- P260 Do not breathe dust/fume.
- P261 Avoid breathing dust/fume.
- P271 Use only outdoors or in a well-ventilated area.

- P280 Wear protective gloves/protective clothing/eye protection/face protection.

2) Response

- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.

3) Storage

- P407 Maintain air gap between stacks/pallets.
- P413 Store bulk masses greater than designate the capacity at temperatures not exceeding designate the temperature.
- P420 Store away from other materials.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

○ **NFPA grade (0 ~ 4 level)**

- Health : 1 , Flammability : 1, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Graphite	-	7782-42-5	100

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Avoid inhalation of materials or combustion by-products.
- Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Wear proper personal protective apparatus as indicated in Section 8 and avoid skin contact and inhalation.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small liquid state spills: Appropriate container for disposal of spilled material collected.
- Put the spilled material in an appropriate containers and clean the contaminated area

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Wash thoroughly after handling.
- Since emptied containers retain product residue(vapor, liquid, solid) follow all MSDS and label warnings even after container is emptied.
- Get the manual before use.
- Operators should wear antistatic footwear and clothing.

B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Do not apply direct heat.
- Do not apply any physical shock to container.
- Avoid direct sunlight.
- No open fire.
- Collected them in sealed containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

○ **ACGIH TLV**

- [Graphite] : TWA, 2 mg/m3, Respirable particulate mass

○ **OSHA PEL**

- [Graphite]: 15 mppcf (Graphite, Natural)/15 mg/m3 (Total dust), 5 mg/m3 (Respirable fraction)(Graphite, syntheric)

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

○ **Respiratory protection**

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Dust, mist, fume-purifying respiratory protection
- Air-purifying respirator with high-efficiency particulate filtering
- Any respiratory protection with a electromotion fan(for dust, mist, fume-purifying)
- Self-contained breathing apparatus with a corpuscle filter of high efficiency
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

○ **Eye protection**

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

○ **Hand protection**

- Wear appropriate chemical resistant glove.

○ **Skin protection**

- Wear appropriate chemical resistant protective clothing.

○ **Others**

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Solid(Other)
- Color	black and gray
B. Odor	odorless
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	>600℃
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	insoluble in water
M. Vapour density	Not available
N. Specific gravity(Relative density)	Not available
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	12.011

10. STABILITY AND REACTIVITY

A. Chemical Stability

- May form explosive mixture.

B. Possibility of hazardous reactions

- Contact with other combustible material may cause fire.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

○ **(Respiratory tracts)**

- Not available

○ **(Oral)**

- Not available

○ **(Eye·Skin)**

- Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

○ **Acute toxicity**

*** Oral**

- [Graphite] : LD50 >2000 ㎎/㎏ Rat (OECD Guideline 423 ,GLP)

*** Dermal**

- Not available

*** Inhalation**

- [Graphite] : Dust LC50 > 2 ㎎/ℓ 4 hr Rat (OECD Guideline 403, GLP)

○ **Skin corrosion/irritation**

- Not available

○ **Serious eye damage/irritation**

- Not available

○ **Respiratory sensitization**

- Not available

○ **Skin sensitization**

- Not available

○ **Carcinogenicity**

*** IARC**

- Not available

*** OSHA**

- Not available

*** ACGIH**

- Not available

*** NTP**

- Not available

*** EU CLP**

- Not available

○ **Germ cell mutagenicity**

- Not available

○ **Reproductive toxicity**

- Not available

○ **STOT-single exposure**

- Not available

○ **STOT-repeated exposure**

- May cause damage to organs through prolonged or repeated exposure

○ **Aspiration hazard**

- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- [Graphite] : LC50 > 100 ㎎/ℓ 96 hr (Danio rerio (OECD Guideline 203,GLP)

○ **Crustaceans**

- [Graphite] : EC50 > 100 ㎎/ℓ 48 hr Daphnia magna (OECD Guideline 202 ,GLP)

○ **Algae**

- [Graphite] : ErC50 > 100 ㎎/ℓ 72 hr (Pseudokirchnerella subcapitata, (OECD Guideline 201,GLP)

B. Persistence and degradability

○ **Persistence**

- Not available

○ **Degradability**

- Not available

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- Not available

○ **Biodegration**

- Not available

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designated waste is mixed, it is difficult to treat separately, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.

B. Special precautions for disposal

- The user of this product must dispose by oneself or entrust it to a waste disposer, a person who recycles other's waste or establishes and operates waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 1361

B. Proper shipping name

- CARBON, ANIMAL OR VEGETABLE ORIGIN

C. Hazard Class

- 4.2

D. IMDG CODE/IATA DGR Packing group

- II

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-A (General fire schedule)
- EmS SPILLAGE SCHEDULE : S-J (Wetted explosives and certain self-heating substances)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ **POPs Management Law**

- Not applicable

○ **Information of EU Classification**

*** Classification**

- Not applicable

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- Not applicable

*** EPCRA Section 302 (40CFR355.30)**

- Not applicable

*** EPCRA Section 304 (40CFR355.40)**

- Not applicable

*** EPCRA Section 313 (40CFR372.65)**

- Not applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2019-03-07

C. Revision number and Last date revised

- 2 times, 2026-04-08

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).